



IRONBULL

A NEW BREED OF TRAILERS

Available Lengths: 10', 12', 14', 16'

Available GVW: 7k, 10k, 14k, 21k

Available Widths: 5', 6', 7'



STANDARDS

14,000 LB GVWR
 7,000 LB GAWR
 4,650 LB WEIGHT (83"x14")
 9,350 LB CAPACITY (83"x14")
 10 GAUGE SIDES & FLOOR
 LIFETIME LED LIGHTS
 7,000 LB DROP LEG JACK
 6" I-BEAM FRAME
 SCISSOR HOIST

2 5/16" ADJUSTABLE COUPLER
 235/80 R16 LRE RADIAL TIRES
 SLIPPER SPRING SUSPENSION
 2-7K CAMBERED DEXTER AXLES
 NEV-R-ADJUST BRAKES
 4 STANDARD 3" D-RINGS
 DOUBLE ACTING HYDRAULIC
 INSULATED WIRE HARNESS
 AVAILABLE FRONT TOOLBOX

STANDARD STAKE POCKETS
 STANDARD MESH TARP
 POWDER COATED
 THREE WAY GATE
 FLOW CONTROL VALVE
 LED VOLTAGE INDICATOR
 7-WAY PLUG
 BATTERY CHARGER
 E-Z LUBE HUBS



SHERWIN-WILLIAMS
Product Finishes



TecNiq



SPECIFICATIONS

GVWR	7000 Lbs	9900 Lbs	14000 Lbs (Best Seller)	21000 Lbs
GAWR	3500 Lb Tandem	5200 Lb Tandem	7000 Lb Tandem	7000 Lb Triple
Lengths	10'	10', 12'	12', 14', 16'	16'
Widths	60"	60", 72"	83"	83"
Coupler	2" A-Frame	2 5/16" Adjustable	2 5/16" Adjustable	2 5/16" Adjustable
Gooseneck	N/A	N/A	10" I-Beam (12 Lbs/ft)	10" I-Beam (12 Lbs/ft) 12" Riser
Safety Chains	1/4" Grd 30	1/4" Grd 70	5/16" Grd 70	3/8" Grd 70
Jack	7000 Lb Drop Leg	7000 Lb Drop Leg	7000 Lb Drop Leg	2-10k Drop Leg Spring Return
Floor	10 Gauge	10 Gauge	10 Gauge	10 Gauge
Sides	18" 10 Gauge 1 Piece	18" (24" over 60" wide) 10 Gauge 1 Piece	24" 10 Gauge 1 Piece	24" 10 Gauge 1 Piece
Lifting Hoist	Scissor	Scissor	Scissor	Scissor
Tongue	6" I-Beam	6" I-Beam	6" I-Beam	6" I-Beam
Frame	6" I-Beam	6" I-Beam	6" I-Beam	6" I-Beam
Runners	3/16" Full Bed	3/16" Full Bed	3/16" Full Bed	3/16" Full Bed
Bed Frame	4" Tubing	4" Tubing	6" Tubing	6" Tubing
Fenders	14 Gauge Diamond Plate	14 Gauge Diamond Plate	14 Gauge Diamond Plate	14 Gauge Diamond Plate
Axles	Tandem	Tandem	Tandem	Triple
Suspension	Multi-Leaf Spring Eye to Eye	Multi-Leaf Eye to Eye Spring w/ Equalizer	Multi-Leaf Slipper Spring w/ Equalizer	Multi-Leaf Slipper Spring w/ Equalizer
Brakes	2 Electric Nev-R-Adjust	2 Electric Nev-R-Adjust	2 Electric Nev-R-Adjust	3 Electric Nev-R-Adjust
Tires	205/75 R15 LRD	205/75 R15 LRD (225/75 R15 LRD over 60")	235/80 R16 LRE	235/80 R16 LRE
Wheels	15" Silver Mod	16" Silver Mod	16" Silver Mod	16" Silver Mod
Lights	Lifetime LED	Lifetime LED	Lifetime LED	Lifetime LED
Ramps	5' Optional	5' Optional / 6.5' Optional (over 60" wide)	6.5' Optional	6.5' Optional
Coating	Powder Coat	Powder Coat	Powder Coat	Powder Coat

OPTIONS

FRONT TOOL BOX	SPARE TIRE MOUNT	SOLAR CHARGER
SLIDE IN RAMPS	REAR SUPPORT STANDS	24" EXTENSIONS
10K JACK	ADDITIONAL D-RINGS	36" SIDES
WIRELESS REMOTE	COLD WEATHER HARNESS	48" SIDES

