

# FLG22 MODEL



# FLG22 MODEL

22k Gooseneck Low-Pro Equipment Trailer

22k Gooseneck Low-Pro Equipment Trailer

OPTIONAL



## 2022 FLG22

Iron Bull Goosenecks are some of the most rugged and longest lasting units in service today. Low-Pro, pierced frame design lowers the deck 3" providing a lower center of gravity, more stable cornering and a lower loading angle for equipment.



NOW STANDARD  
DEXTER HDSS  
SUSPENSION SYSTEM



2022 BASE SPECS						
WIDTH	LENGTH	GVWR	AXLES	TIRE/WHEEL	FRAME	WEIGHT
102	20	22000	2 X 10,000 lb	235/80R16 8 Hole	12" I-Beam	6300
102	22	22000	2 X 10,000 lb	235/80R16 8 Hole	12" I-Beam	6600
102	24	22000	2 X 10,000 lb	235/80R16 8 Hole	12" I-Beam	6920
102	25	22000	2 X 10,000 lb	235/80R16 8 Hole	12" I-Beam	7310
102	26	22000	2 X 10,000 lb	235/80R16 8 Hole	12" I-Beam	7410
102	28	22000	2 X 10,000 lb	235/80R16 8 Hole	12" I-Beam	7640
102	30	22000	2 X 10,000 lb	235/80R16 8 Hole	12" I-Beam	7855
102	32	22000	2 X 10,000 lb	235/80R16 8 Hole	12" I-Beam	8105
102	34	22000	2 X 10,000 lb	235/80R16 8 Hole	12" I-Beam	8350
102	36	22000	2 X 10,000 lb	235/80R16 8 Hole	12" I-Beam	8675
102	38	22000	2 X 10,000 lb	235/80R16 8 Hole	12" I-Beam	8900
102	40	22000	2 X 10,000 lb	235/80R16 8 Hole	12" I-Beam	9200

\*WEIGHT OF UNITS ARE APPROXIMATES ONLY AND SUBJECT TO CHANGE DEPENDING ON OPTIONS

Photos may include optional features.

## OPTIONAL FEATURES

CODE	DESCRIPTION	CODE	DESCRIPTION
10HS2	2 - 10000 Lb Electric Over Hydraulic Disc Axles	K21	12" Crossmembers (per ft)
12ES2	2 - 12000 Lb Electric Brake Axles	H72	6' Spread Axles
12HS2	2 - 12000 Lb Electric Over Hydraulic Disc Brake Axles	D60	Deck Over Neck
15ES2	2 - 15000 Lb Electric Brake Axles	T42	Side Tool Box
15AS2	2 - 15000 Lb Air Ride Axles	J55	Drop-Leg Jack (2-Speed)
10ES3	3 - 10000 Lb Electric Brake Axles	W91	Cold Weather Harness
10HS3	3 - 10000 Lb Electric Over Hydraulic Brake Axles	J56	2 - 12k Hydraulic Jacks
12ES3	3 - 12000 Lb Electric Brake Axles	U30	Weld On Ratchet Track Only (per ft)
12HS3	3 - 12000 Lb Electric Over Hydraulic Brake Axles	U32	Weld On Ratchets Every 5' (per ft)
D30	Rampage Ramps (2 - 40" Flip-Over Ramps with 5' Self Cleaning Dove)	U31	Weld On Track with Adjustable Ratchets Every 5' (ft)
D35	5' Self Cleaning Dove Tail with Slide-in Ramps	T06	14-Ply 235/85 Tire Upgrade (ea.)
D31	5' Self Cleaning Dove Tail with 2 Flip-Over Ramps	T21	17.5"x6.75" Tire Upgrade (ea.)
D32	5' Self Cleaning Dove Tail with 3. Flip-Over Ramps	U52	Winch Plate 1/2" (In Neck)
S01	Tube Rear Support Stands		

## STANDARD FEATURES

- 12" I-Beam Frame and Neck (19 lbs/ft)
- 2 5/16" Adjustable Coupler
- 3" Structural Crossmembers
- 2.5 x 2.5 Front Bumper Rail
- Lockable Full Neck Width Tool Box
- Rub Rail, Stake Pockets & Pipe Spools
- Standard Torque Tube & Underframe Bridge
- Dexter HDSS Standard
- 2-10K Nev-R-Adjust Electric Brake Axles
- Multi-leaf Slipper Spring Suspension
- E-Z Lube Hubs
- 25" Gooseneck Box
- 8' Slide-in Ramps
- 2-10k Drop-Leg Jack
- Treated Pine 2x6 Floor
- 4 Standard 3" D-Rings
- Black Mod Wheels \*
- 235/80R16 Radial Tires
- Lifetime LED Lighting
- All Lighting DOT Approved
- Molded Sealed Harness with Resistors
- 7-Way Receiver Female Plug with Adapter
- Powdura Powder Coat & One Cure Primer

## 2021 FLG22 Optional Features



Rampage Ramps



Triple Axle Configurations



2 - 12K Electric Brake Axles

BUILD A QUOTE ONLINE AT NORSTARCOMPANY.COM

GRAB A BULL BY THE HORNS

5500 FM 38N, BROOKSTON, TX 75421