DTG MODEL



6" I-Beam Gooseneck Dump Trailer



STANDARD FEATURES

6" I-Beam Frame (12lbs/ft)
12" I-Beam Neck and Risers
7 Gauge Steel Flooring
4" Tubing Bed Frame
Full Length Bed Runners and Ramp Pockets
10 Gauge 24" Steel Sides
Standard Retractable Tarp Kit
Dual 10k Drop-Leg Jacks
2 5/16" Adjustable Coupler
Cambered Brake Axles
Multi-leaf Slipper Spring Suspension
Black Mod Wheels
Radial Tires
Spare Tire Mount
Slide-in Ramps

Rear Support Stand Bracket
Three-Way Spreader Gate
Powdura Powder Coat & One Cure Primer
Scissor Hoist with 516 Cylinder
Double Acting Pump Unit w/ Gravity Down
Flow Control Valve
Locking Pump Box
Standard Stake Pockets
Weld On Diamond Plate Fenders
Four Floor Mounted 5/8" D-Rings
DOT Approved Lifetime LED Lighting
Molded Sealed Harness with Resistors
LED Voltage Indicater in Remote
Built-In 5 amp Battery Charger
7-Way Receiver Female Plug with Adapter



DTG MODEL

6" I-Beam Gooseneck Dump Trailer

2023 BASE SPECS						
WIDTH	LENGTH	GVWR	AXLES	TIRE/WHEEL	SIDES	WEIGHT
83	12	14000	2 X 7000 lb	235/80R16 8 Hole	24"	4915
83	14	14000	2 X 7000 lb	235/80R16 8 Hole	24"	5195
. 83	16	14000	2 X 7000 lb	235/80R16 8 Hole	24"	5400
83	16	21000	3 X 7000 lb	235/80R16 8 Hole	24"	5920

*WEIGHT OF UNITS ARE APPROXIMATES ONLY AND SUBJECT TO CHANGE DEPENDING ON OPTIONS

OPTIONAL FEATURES						
CODE	DESCRIPTION	CODE	DESCRIPTION			
082	Tandem 8k Axles	W91	Cold Weather Harness			
R50	Ramps (14k, 21k) 16" x 80"	J55	2 Speed 10K Drop-Leg Jacks			
D60	Deck Over Neck	J52	2 12K Hydraulic Jacks			
S01	Rear Stabilizer Jacks	S90	Solar Charger (1.5Amp)			
X90	24" Solid Side Extensions	R90	Wireless Remote			
S61	3' Side Walls	V54	3-Way Pump			
S62	4' Side Walls	V53	3 Stage Telescopic Cylinder			



Available Rear Supports



7 Gauge Floor Standard



Available Side Extensions



Full Length Bed Runners



3' & 4' Sides Available



Triple Axle Avalable

Photos may include optional features.