FHG22 MODEL



22k Gooseneck Hydraulic Dove Trailer



STANDARD FEATURES

12" I-Beam Frame and Neck (19 lbs/ft)
2 5/16" Adjustable Coupler
3" Structural Crossmembers
Rub Rail, Stake Pockets & Pipe Spools
HDSS Standard
2-10K Electric Brake Axles
Multi-leaf Slipper Spring Suspension
E-Z Lube Hubs
Standard Torque Tube & Pipe Bridge
Powdura Powder Coat & One Cure Primer
Spare Tire & Mount

2 - 10k Drop-Leg Jacks
Treated Pine 2" x 6" Floor
4 Standard 3" D-Rings
Black Mod Wheels
235/80R16 Radial Tires
Lifetime LED Lighting
All Lighting DOT Approved
Molded Sealed Harness with Resistors
7-Way Receiver Female Plug with Adapter



FHG22 MODEL

22k Gooseneck Hydraulic Dove Trailer

2023 BASE SPECS									
WIDTH	LENGTH	GVRW	AXLES	TIRE/WHEEL	FRAME	WEIGHT			
102	28	22000	2 X 10,000 lb	235/80R16 8 Hole	12" (19lb/ft)	7620			
102	30	22000	2 X 10,000 lb	235/80R16 8 Hole	12" (19lb/ft)	7945			
102	32	22000	2 X 10,000 lb	235/80R16 8 Hole	12" (19lb/ft)	8105			
102	34	22000	2 X 10,000 lb	235/80R16 8 Hole	12" (19lb/ft)	9490			
102	36	22000	2 X 10,000 lb	235/80R16 8 Hole	12" (19lb/ft)	9690			
102	38	22000	2 X 10,000 lb	235/80R16 8 Hole	12" (19lb/ft)	9890			
102	40	22000	2 X 10,000 lb	235/80R16 8 Hole	12" (19lb/ft)	10000			

*WEIGHT OF UNITS ARE APPROXIMATES ONLY AND SUBJECT TO CHANGE DEPENDING ON OPTIONS

OPTIONAL FEATURES							
CODE	DESCRIPTION	CODE	DESCRIPTION				
10HS2	2 - 10000 Lb Electric Over Hydraulic Disc Axles	J56	2 12k Hydraulic Jacks				
12ES2	2 - 12000 Lb Electric Brake Axles	H72	6' Spread Axles				
12HS2	2 - 12000 Lb Electric Over Hydraulic Disc Brake	K21	12" Crossmembers (per ft)				
15ES2	2 - 15000 Lb Electric Brake Axles	D60	Deck Over Neck				
15AS2	2 - 15000 Lb Air Ride Axles	T42	Additional Side Tool Box (ea.)				
10ES3	3 - 10000 Lb Electric Brake Axles	J55	2 Speed Drop-Leg Jacks				
10HS3	3 - 10000 Lb Electric Over Hydraulic Brake Axles	W91	Cold Weather Harness				
12ES3	3 - 12000 Lb Electric Brake Axles	T21	17.5"x6.75" Tire Upgrade (ea.)				
12HS3	3 - 12000 Lb Electric Over Hydraulic Brake Axles	U30	Weld On Ratchet Track Only (per ft)				
D96	9' Hydraulic Dove Tail with Cleats on OUTSIDE ONLY	U32	Weld On Ratchets Every 5' (per ft)				
D97	9' Hydraulic Dove Tail with Cleats FULL TAIL	U33	Weld On Track with Adjustable Ratchets Every 5'				
D98	9' Hydraulic Dove SELF CLEANING OUTSIDE ONLY	R90	Wireless Remote				
D99	9' Hydraulic Dove FULL SELF CLEANING	U52	Winch Plate 1/2" (in neck)				
D95	9' Hydraulic Dove Tail Blackwood OUTSIDE ONLY	T06	14-Ply 235/85 Tire Upgrade (ea.)				







Up to 15k Axles

D98 Self Cleaning with Cleats Outside