

FLP22 MODEL



22k Deckover Pintle Trailer

OPTIONAL



Treated Pine Flooring

Diamond Plate Fenders



Self-Cleaning Dovetail

Lifetime LED Lighting

2023 FLP22

We designed our FLP22 Heavy Pintle with the idea of making things easier for the customer. With up to 3 15k axles, optional Rampage Ramps, 3" 60k pintle eye coupler and a self-cleaning dovetail, the FLP22 makes hauling even the heaviest machinery a smooth ride.



Optional 3rd Axle

Powdura Powder Coat and One Cure Primer

Rub Rail and Stake Pockets

12" I-Beam Pierced Frame

Torque Tube

12" I-Beam Frame (19 lbs/ft)

Spare Tire Mount

60k Pintle Eye Coupler

33" Deck Height

Radial Tires

Cambered HDSS Electric Brake Axles

Dual Oversized Stirrup Steps

10k Drop-Leg Jack

23.5" - 32.5" Coupler Height

Under Frame Bridge

STANDARD FEATURES

- 12" I-Beam Frame (19 lbs/ft)
- 60k Pintle Eye Coupler
- 3" Structural Crossmembers
- 2.5 x 2.5 Front Bumper Rail
- Rub Rail, Stake Pockets & Pipe Spools
- Standard Torque Tube & Underframe Bridge
- Heavy Duty Suspension System Standard
- 2-10K Electric Brake Axles
- Multi-leaf Slipper Spring Suspension
- E-Z Lube Hubs

- 8' Slide-in Ramps
- 2-10k Drop-Leg Jacks
- Treated Pine 2x6 Floor
- 4 Standard 3" D-Rings
- Black Mod Wheels
- 235/80R16 Radial Tires
- Lifetime LED Lighting
- All Lighting DOT Approved
- Molded Sealed Harness with Resistors
- 7-Way Receiver Female Plug with Adapter
- Powdura Powder Coat & One Cure Primer

BUILD A QUOTE ONLINE AT NORSTARCOMPANY.COM

GRAB A BULL BY THE HORNS

22k Deckover Pintle Trailer

2023 BASE SPECS

WIDTH	LENGTH	GVWR	AXLES	TIRE/WHEEL	FRAME	WEIGHT
102	20	22000	2 X 10,000 lb	235/80R16 8 Hole	12" (19lb/ft)	6270
102	22	22000	2 X 10,000 lb	235/80R16 8 Hole	12" (19lb/ft)	6456
102	24	22000	2 X 10,000 lb	235/80R16 8 Hole	12" (19lb/ft)	6550
102	25	22000	2 X 10,000 lb	235/80R16 8 Hole	12" (19lb/ft)	6656
102	26	22000	2 X 10,000 lb	235/80R16 8 Hole	12" (19lb/ft)	6770
102	28	22000	2 X 10,000 lb	235/80R16 8 Hole	12" (19lb/ft)	6856
102	30	22000	2 X 10,000 lb	235/80R16 8 Hole	12" (19lb/ft)	7056
102	32	22000	2 X 10,000 lb	235/80R16 8 Hole	12" (19lb/ft)	7256
102	34	22000	2 X 10,000 lb	235/80R16 8 Hole	12" (19lb/ft)	7456
102	36	22000	2 X 10,000 lb	235/80R16 8 Hole	12" (19lb/ft)	7656
102	38	22000	2 X 10,000 lb	235/80R16 8 Hole	12" (19lb/ft)	7856
102	40	22000	2 X 10,000 lb	235/80R16 8 Hole	12" (19lb/ft)	8156

*WEIGHT OF UNITS ARE APPROXIMATES ONLY AND SUBJECT TO CHANGE DEPENDING ON OPTIONS

Photos may include optional features.

OPTIONAL FEATURES

CODE	DESCRIPTION	CODE	DESCRIPTION
10HS2	2 - 10000 Lb Electric Over Hydraulic Disc Axles	K21	12" Crossmembers (per ft)
12ES2	2 - 12000 Lb Electric Brake Axles	H72	6' Spread Axles
12HS2	2 - 12000 Lb Electric Over Hydraulic Disc Brake Axles	S01	Tube Rear Support Stands
15ES2	2 - 15000 Lb Electric Brake Axles	T42	Side Tool Box
15AS2	2 - 15000 Lb Air Ride Axles	T46	Tongue Mount Toolbox
10ES3	3 - 10000 Lb Electric Brake Axles	J55	Drop-Leg Jack (2-Speed)
10HS3	3 - 10000 Lb Electric Over Hydraulic Brake Axles	W91	Cold Weather Harness
12ES3	3 - 12000 Lb Electric Brake Axles	U50	Winch Plate (Floor)
12HS3	3 - 12000 Lb Electric Over Hydraulic Brake Axles	U30	Weld On Ratchet Track Only (per ft)
D30	Rampage Ramps (2-40" Flip-Over Ramps with 5' Self Cleaning Dove	U32	Weld On Ratchets Every 5' (per ft)
D35	5' Self Cleaning Dove Tail with Slide-in Ramps	U31	Weld On Track with Adjustable Ratchets Every 5' (ft)
D31	5' Self Cleaning Dove Tail with 2 Flip-Over Ramps	T06	14-Ply 235/85 Tire Upgrade (ea.)
D32	5' Self Cleaning Dove Tail with 3. Flip-Over Ramps	T21	17.5"x6.75" Tire Upgrade (ea.)



5500 FM 38N, BROOKSTON, TX 75421