

102^{**} Bed Width

20² Bed Length

24,900 lbs ____

GVWR

17,000 lbs

Load Capacity

STANDARD FEATURES

- 2 10,000 lb Premium Electric Brake Axles
- ST235/80 R16 LRE Radial Tires
- 12" 19lb I-Beam Frame
- 12" 19lb I-Beam Riser
- 12" 19lb I-Beam Neck
- 48" 10 Ga Dump Sides
- 25k 2 5/16" Adjustable Gooseneck Coupler
- 2 10k Drop Leg Jacks

- Front Full Tool Box
- 3 Stage Telescopic Cylinder (12 tons x 144")
- T80 Tarp System (Front Mount Galvanized Manual)
- Dual Mud Flaps
- Sealed Wiring Harness
- D-Rings 3 x 5/8" (8 Each)
- Spare Tire ST 235/80 R16 LRE 10 Ply
- Stake Pockets

- Flow Control Valve
- 2" x 6" Top Rail & Up Right Tubing
- Side Step Plate & Ladder
- Heavy Duty Suspension System
- Heavy Duty 16" x 96" Slide-in Ramps
- Powder Coat & Primer
- 38" Deck Height

5500 FM 38N, BROOKSTON, TX 75421 • NORSTARCOMPANY.COM

OPTIONAL UPGRADE IZK AXLES FOR 24,900 GVWR



96" Long 2 x 3 1/4" Tubing Ramps



Heavy Duty Suspension System



Side Step Ladder & Barn Doors



Square Bottom Floor



12" 19 lb Frame, Neck & Risers



Locking Battery & Pump Box