

5500 FM 38N, BROOKSTON, TX 75421 • NORSTARCOMPANY.COM

## BASE SPECS

WIDTH	LENGTH	GVWR	AXLES	TIRE/WHEEL	FRAME	WEIGHT
83	12	14,999	2 x 7,000 lb	235/80R16 8 Hole	8" I-Beam	4,870
83	14	14,999	2 x 7,000 lb	235/80R16 8 Hole	8" I-Beam	5,170
83	16	14,999	2 x 7,000 lb	235/80R16 8 Hole	8" I-Beam	5,478

\*WEIGHT OF UNITS ARE APPROXIMATES ONLY AND SUBJECT TO CHANGE DEPENDING ON OPTIONS

83" \_\_\_ 12' - 16' \_\_\_ 14,999 lbs \_\_\_ 9,521 - 10,129 lbs

Bed Width Bed Lengths GVWR Load Capacity

## STANDARD FEATURES

- Side Armor™ Body Design
- 235/80R16 Radial Tires
- Reinforced Top Rail
- Toolbox & Front Jack Bracket
- 8" I-Beam Frame & Tongue (10 lbs/ft)
- 4" Tubing Bed Frame
- 7 Gauge Steel Flooring
- 3 x 3/16" Channel Crossmembers
- 10 Gauge 24" Steel Sides
- Standard Retractable Tarp Kit
- Weld On Diamond Plate Fenders
- 10k Drop-Leg Jack

- 2 5/16" Adjustable Auto Latching Coupler
- 7k or 8k Cambered Brake Axles
- Multi-leaf Slipper Spring Suspension
- Black Mod Wheels\*
- Spare Tire Mount
- Slide-in Ramps
- Rear Support Stand Bracket
- Three-Way Spreader Gate
- Powder Coat & Primer
- Scissor Hoist with 516 Cylinder
- Double Acting Pump Unit w/ Gravity Down

- Flow Control Valve
- Locking Pump Box
- Standard Stake Pockets
- Four Floor Mounted 1/2" D-Rings
- DOT Approved Lighting
- · Lifetime LED Lighting
- Molded Sealed Harness with Resistors
- LED Voltage Indicater in Remote
- Built-In 5 amp Battery Charger
- 7-Way Receiver Female Plug with Adapter





Side Armor™ System



7 Gauge Steel Flooring



516 Scissor Hoist



3 Way Spreader Gate