

FHG22 MODEL

Gooseneck Hydraulic Dove Trailer



IRONBULL

A NEW BREED OF TRAILERS



Our FHG comes equipped with our patented revolutionary design of the traditional hydraulic dove tail and is sure to be the biggest workhorse in your stable.



HDSS

HEAVY DUTY
SUSPENSION SYSTEM



102"
Deck Width

28' - 40'
Deck Lengths

23,900 lbs
GVWR

13,970 - 15,545 lbs
Load Capacity

STANDARD FEATURES

- 12" I-Beam Frame and Neck (19 lbs/ft)
- 235/80R16 Radial Tires
- 2 5/16" Adjustable Coupler
- 3" Structural Crossmembers
- Rub Rail, Stake Pockets & Pipe Spools
- Heavy Duty Suspension System Standard
- 2-10k Electric Brake Axles

- Multi-leaf Slipper Spring Suspension
- E-Z Lube Hubs
- Standard Torque Tube & Pipe Bridge
- Powder Coat & Primer
- Spare Tire & Mount
- 2 - 10k Drop-Leg Jacks
- Treated Pine 2" x 8" Floor

- 4 Standard 3" D-Rings
- Black Mod Wheels*
- Lifetime LED Lighting
- All Lighting DOT Approved
- Molded Sealed Harness with Resistors
- 7-Way Receiver Female Plug with Adapter
- 34" Deck Height

5500 FM 38N, BROOKSTON, TX 75421 • NORSTARCOMPANY.COM

BASE SPECS

WIDTH	LENGTH	GVWR	AXLES	TIRE/WHEEL	FRAME	WEIGHT
102	28	23,900	2 x 10,000 lb	235/80R16 8 Hole	12" (19lb/ft)	8,355
102	30	23,900	2 x 10,000 lb	235/80R16 8 Hole	12" (19lb/ft)	8,605
102	32	23,900	2 x 10,000 lb	235/80R16 8 Hole	12" (19lb/ft)	8,880
102	34	23,900	2 x 10,000 lb	235/80R16 8 Hole	12" (19lb/ft)	9,130
102	36	23,900	2 x 10,000 lb	235/80R16 8 Hole	12" (19lb/ft)	9,405
102	38	23,900	2 x 10,000 lb	235/80R16 8 Hole	12" (19lb/ft)	9,655
102	40	23,900	2 x 10,000 lb	235/80R16 8 Hole	12" (19lb/ft)	9,930

*WEIGHT OF UNITS ARE APPROXIMATES ONLY AND SUBJECT TO CHANGE DEPENDING ON OPTIONS

FHG22 OPTIONAL FEATURES

CODE DESCRIPTION

- 10HS2 2 - 10,000 lb Electric Over Hydraulic Disc Axles
- 12ES2 2 - 12,000 lb Electric Brake Axles
- 12HS2 2 - 12,000 lb Electric Over Hydraulic Disc Brake
- 15ES2 2 - 15,000 lb Electric Brake Axles
- 15AS2 2 - 15,000 lb Air Ride Axles
- 10ES3 3 - 10,000 lb Electric Brake Axles
- 10HS3 3 - 10,000 lb Electric Over Hydraulic Brake Axles
- 12ES3 3 - 12,000 lb Electric Brake Axles
- 12HS3 3 - 12,000 lb Electric Over Hydraulic Brake Axles
- D96 9' Hydraulic Dove Tail with Cleats on OUTSIDE ONLY
- D97 9' Hydraulic Dove Tail with Cleats FULL TAIL
- D98 9' Hydraulic Dove SELF CLEANING OUTSIDE ONLY
- D99 9' Hydraulic Dove FULL SELF CLEANING
- D95 9' Hydraulic Dove Tail Blackwood OUTSIDE ONLY
- J56 2 - 12k Hydraulic Jacks
- H72 6' Spread Axles

CODE DESCRIPTION

- K21 12" Crossmembers (per ft)
- D60 Deck Over Neck
- T42 Additional Side Tool Box (ea.)
- J55 2 Speed Drop-Leg Jacks
- W91 Cold Weather Harness
- T21 17.5" x 6.75" Tire Upgrade (ea.)
- U30 Weld On Ratchet Track Only (per ft)
- U32 Weld On Ratchets Every 5' (per ft)
- U31 Weld On Track with Adjustable Ratchets Every 5'
- R90 Wireless Remote
- U52 Winch Plate 1/2" (in neck)
- T06 14-Ply 235/85 Tire Upgrade (ea.)



Blackwood Floor Option



Up to 15k Axles



D98 Self Cleaning w/ Cleats Outside

WHERE DURABILITY MEETS AFFORDABILITY