

FLG22 MODEL

Gooseneck Low-Pro Equipment Trailer



IRONBULL

A NEW BREED OF TRAILERS



Iron Bull Goosenecks are some of the most rugged and longest lasting units in service today. Low-Pro, pierced frame design lowers the deck 3" providing a lower center of gravity, more stable cornering and a lower loading angle for equipment.



HDSS

HEAVY DUTY
SUSPENSION SYSTEM



102" Deck Width **20' - 40'** Deck Lengths **23,900 lbs** GVWR **14,415 - 17,824 lbs** Load Capacity

STANDARD FEATURES

- 12" I - Beam Frame and Neck (19 lbs/ft)
- 235/80R16 Radial Tires
- Low Pro Deck
- 2 5/16" Adjustable Coupler
- 3" Structural Crossmembers
- 2.5 x 2.5 Front Bumper Rail
- Lockable Full Neck Width Tool Box
- Rub Rail, Stake Pockets & Pipe Spools
- Standard Torque Tube & Underframe Bridge
- Heavy Duty Suspension System Standard
- 2 - 10k Electric Brake Axles
- Multi-leaf Slipper Spring Suspension
- E-Z Lube Hubs
- 25" Gooseneck Box
- 8' Slide-in Ramps
- 2 - 10k Drop-Leg Jack
- Treated Pine 2" x 8" Floor
- 4 Standard 3" D-Rings
- Black Mod Wheels*
- Spare Tire & Mount
- Lifetime LED Lighting
- All Lighting DOT Approved
- Molded Sealed Harness with Resistors
- 7-Way Receiver Female Plug with Adapter
- Powder Coat & Primer
- 34" Deck Height

5500 FM 38N, BROOKSTON, TX 75421 • NORSTARCOMPANY.COM

BASE SPECS

WIDTH	LENGTH	GVWR	AXLES	TIRE/WHEEL	FRAME	WEIGHT
102	20	23,900	2 x 10,000 lb	235/80R16 8 Hole	12" (19lb/ft)	
102	22	23,900	2 x 10,000 lb	235/80R16 8 Hole	12" (19lb/ft)	6,076
102	24	23,900	2 x 10,000 lb	235/80R16 8 Hole	12" (19lb/ft)	6,376
102	25	23,900	2 x 10,000 lb	235/80R16 8 Hole	12" (19lb/ft)	6,526
102	26	23,900	2 x 10,000 lb	235/80R16 8 Hole	12" (19lb/ft)	6,676
102	28	23,900	2 x 10,000 lb	235/80R16 8 Hole	12" (19lb/ft)	6,976
102	30	23,900	2 x 10,000 lb	235/80R16 8 Hole	12" (19lb/ft)	7,276
102	32	23,900	2 x 10,000 lb	235/80R16 8 Hole	12" (19lb/ft)	7,626
102	34	23,900	2 x 10,000 lb	235/80R16 8 Hole	12" (19lb/ft)	7,996
102	36	23,900	2 x 10,000 lb	235/80R16 8 Hole	12" (19lb/ft)	8,396
102	38	23,900	2 x 10,000 lb	235/80R16 8 Hole	12" (19lb/ft)	8,796
102	40	23,900	2 x 10,000 lb	235/80R16 8 Hole	12" (19lb/ft)	9,485

*WEIGHT OF UNITS ARE APPROXIMATES ONLY AND SUBJECT TO CHANGE DEPENDING ON OPTIONS

FLG22 OPTIONAL FEATURES

CODE DESCRIPTION

10HS2	2 - 10,000 lb Electric Over Hydraulic Disc Axles
12ES2	2 - 12,000 lb Electric Brake Axles
12HS2	2 - 12,000 lb Electric Over Hydraulic Disc Brake
15ES2	2 - 15,000 lb Electric Brake Axles
15AS2	2 - 15,000 lb Air Ride Axles
10ES3	3 - 10,000 lb Electric Brake Axles
10HS3	3 - 10,000 lb Electric Over Hydraulic Brake Axles
12ES3	3 - 12,000 lb Electric Brake Axles
12HS3	3 - 12,000 lb Electric Over Hydraulic Brake Axles
D30	Rampage Ramps (2 - 40" Flip-Over Ramps w 5' Self Cleaning Dove)
D35	5' Self Cleaning Dove Tail with Slide-in Ramps
D31	5' Self Cleaning Dove Tail with 2 Flip-Over Ramps
D32	5' Self Cleaning Dove Tail with 3 Flip-Over Ramps
S01	Tube Rear Support Stands

CODE DESCRIPTION

J55	2 Speed Drop-Leg Jacks
J56	2 - 12k Hydraulic Jacks
H72	6' Spread Axles
K21	12" Crossmembers (per ft)
D60	Deck Over Neck
T42	Additional Side Tool Box (ea.)
W91	Cold Weather Harness
T21	17.5" x 6.75" Tire Upgrade (ea.)
U30	Weld On Ratchet Track Only (per ft)
U32	Weld On Ratchets Every 5' (per ft)
U31	Weld On Track with Adjustable Ratchets Every 5'
U52	Winch Plate 1/2" (in neck)
T06	14-Ply 235/85 Tire Upgrade (ea.)



Rampage Ramps



Triple Axle Configurations



2 - 12k Electric Brake Axles

Photos may include optional features.

WHERE DURABILITY MEETS AFFORDABILITY