FLP22 MODEL

22k Deckover Pintle Trailer





102" Deck Width

Deck Lengths

GVWR

20' - 24' ___ 23,900 lbs ___ 15,744 - 17,630 lbs

Load Capacity

STANDARD FEATURES

- 12" I Beam Frame (19 lbs/ft)
- 235/80R16 Radial Tires
- 60k Pintle Eye Coupler
- 3" Structural Crossmembers
- 2.5 x 2.5 Front Bumper Rail
- Rub Rail, Stake Pockets & Pipe Spools
- Standard Torque Tube & Underframe Bridge
- Heavy Duty Suspension System Standard
- 2 10k Electric Brake Axles
- Multi-leaf Slipper Spring Suspension
- E-Z Lube Hubs
- 8' Slide-in Ramps
- 2 10k Drop-Leg Jacks
- Treated Pine 2" x 8" Floor
- 4 Standard 3" D-Rings

- Black Mod Wheels*
- Lifetime LED Lighting
- All Lighting DOT Approved
- Molded Sealed Harness with Resistors
- 7-Way Receiver Female Plug with Adapter
- Powder Coat & Primer
- 34" Deck Height

5500 FM 38N, BROOKSTON, TX 75421 • NORSTARCOMPANY.COM

BASE SPECS

WIDTH	LENGTH	GVWR	AXLES	TIRE/WHEEL	FRAME	WEIGHT
102	20	23,900	2 x 10,000 lb	235/80R16 8 Hole	12" (19lb/ft)	6,270
102	22	23,900	2 x 10,000 lb	235/80R16 8 Hole	12" (19lb/ft)	6,456
102	24	23,900	2 x 10,000 lb	235/80R16 8 Hole	12" (19lb/ft)	6,550
102	25	23,900	2 x 10,000 lb	235/80R16 8 Hole	12" (19lb/ft)	6,656
102	26	23,900	2 x 10,000 lb	235/80R16 8 Hole	12" (19lb/ft)	6,770
102	28	23,900	2 x 10,000 lb	235/80R16 8 Hole	12" (19lb/ft)	6,856
102	30	23,900	2 x 10,000 lb	235/80R16 8 Hole	12" (19lb/ft)	7,056
102	32	23,900	2 x 10,000 lb	235/80R16 8 Hole	12" (19lb/ft)	7,256
102	34	23,900	2 x 10,000 lb	235/80R16 8 Hole	12" (19lb/ft)	7,456
102	36	23,900	2 x 10,000 lb	235/80R16 8 Hole	12" (19lb/ft)	7,656
102	38	23,900	2 x 10,000 lb	235/80R16 8 Hole	12" (19lb/ft)	7,856
102	40	23,900	2 x 10,000 lb	235/80R16 8 Hole	12" (19lb/ft)	8,156

^{*}WEIGHT OF UNITS ARE APPROXIMATES ONLY AND SUBJECT TO CHANGE DEPENDING ON OPTIONS

FLP22 OPTIONAL FEATURES

CODE	DECUDIDATION	

2 - 10,000 lb Electric Over Hydraulic Disc Axles
2 - 12,000 lb Electric Brake Axles
2 - 12,000 lb Electric Over Hydraulic Disc Brake
2 - 15,000 lb Electric Brake Axles
2 - 15,000 lb Air Ride Axles
3 - 10,000 lb Electric Brake Axles
3 - 10,000 lb Electric Over Hydraulic Brake Axles
3 - 12,000 lb Electric Brake Axles
3 - 12,000 lb Electric Over Hydraulic Brake Axles
Rampage Ramps (2 - 40" Flip-Over Ramps w 5' Self Cleaning Dove
5' Self Cleaning Dove Tail with Slide-in Ramps
5' Self Cleaning Dove Tail with 2 Flip-Over Ramps
5' Self Cleaning Dove Tail with 3 Flip-Over Ramps

CODE DESCRIPTION

S01	Tube Rear Support Stands
J55	2 Speed Drop-Leg Jacks
H72	6' Spread Axles
K21	12" Crossmembers (per ft)
T42	Additional Side Tool Box (ea.)
T46	Tongue Mount Toolbox
W91	Cold Weather Harness

T21 17.5" x 6.75" Tire Upgrade (ea.)
U30 Weld On Ratchet Track Only (per ft)

U32 Weld On Ratchets Every 5' (per ft)
U31 Weld On Track with Adjustable Ratche

U31 Weld On Track with Adjustable Ratchets Every 5'U50 Winch Plate (Floor)

T06 14-Ply 235/85 Tire Upgrade (ea.)





Photos may include optional features.