FXG22 MODEL

22k Tandem Dual Deckover





Tandem Duals



12" 19lb I-Beam Neck

Norstar Gooseneck Trailers deliver the same quality, usablity and reliability as you've come to expect from IronBull. Decades of experience contributed to create one of the most durable trailers available on the market today. Norstar Goosenecks are built to haul and get you there and back again and again.



Deck Width

25' -40' Deck Lengths

GVWR

22,000 lbs ____ 13,005 - 15,210 lbs

Load Capacity

STANDARD FEATURES

- 2 10,000 Lb Electric Brake Axles
- ST235/80 R16 LRE 10 Ply. (Dual)
- 12" 19lb I-Beam Frame & Neck
- 6" Channel Side Rail
- 16" Crossmembers (3" 3.5lb C-channel)
- 5 1/2" Torque Tube
- 102" X 5' Self Cleaning Dove Tail w/ Rampage Ramps
- Under Frame Bridge
- Front Tool Box
- Rub Rails w/Stake Pockets & Pipe Spools
- 2-5/16" Gooseneck Coupler Adjustable Rd. 25K
- Treated Wood Floor
- Spring Loaded Drop Leg Jack 2-10K
- D-Rings 3" x 5/8" Weld On (4 ea)

- Spare Tire ST235/80 R16 LRE 10 Ply. (Dual)
- Mud Flaps with Norstar Logo (Dual Tires)
- Standard Wire Harness
- New Diamond Plate Steps
- Powder Coat & Primer
- One Year Warranty
- 32" Deck Height

5500 FM 38N, BROOKSTON, TX 75421 • NORSTARCOMPANY.COM

BASE SPECS

WIDTH	LENGTH	GVWR	AXLES	TIRE/WHEEL	FRAME	WEIGHT
102	25	22,000	2 x 10,000 lb	ST 235/80R16 LRE	12" (19lb/ft)	6,790
102	26	22,000	2 x 10,000 lb	ST 235/80R16 LRE	12" (19lb/ft)	6,962
102	28	22,000	2 x 10,000 lb	ST 235/80R16 LRE	12" (19lb/ft)	7,297
102	30	22,000	2 x 10,000 lb	ST 235/80R16 LRE	12" (19lb/ft)	7,606
102	32	22,000	2 x 10,000 lb	ST 235/80R16 LRE	12" (19lb/ft)	7,893
102	34	22,000	2 x 10,000 lb	ST 235/80R16 LRE	12" (19lb/ft)	8,179
102	36	22,000	2 x 10,000 lb	ST 235/80R16 LRE	12" (19lb/ft)	8,400
102	38	22,000	2 x 10,000 lb	ST 235/80R16 LRE	12" (19lb/ft)	8,708
102	40	22,000	2 x 10,000 lb	ST 235/80R16 LRE	12" (19lb/ft)	8,995

*WEIGHT OF UNITS ARE APPROXIMATES ONLY AND SUBJECT TO CHANGE DEPENDING ON OPTIONS



Front Toolbox Between Neck



Spare Tire (Standard On Tandem Duals)



Rampage Ramps



LED Lighting