TDP14 MODEL

14k Deckover Tilt Pintle Trailer







Our TDP14 Deckover features an 8" I-Beam tongue and frame. 14k GVWR and dual hydraulic cylinders with optional scissor. The TDP is built to deliver maximum performance and versitility.



ALSO AVAILABLE IN GOOSENECK

102"

____ 14,000 lbs ____ 8,320 - 9,700 lbs

Load Capacity

Deck Width Deck Lengths **GVWR**

STANDARD FEATURES

- 8" I-Beam Frame (10 lbs/ft)
- 235/80R16 Radial Tires
- 2 5/16" Adjustable Auto Latching Coupler
- 3" Structural Crossmembers
- 4" Tube Frame Runners
- Rub Rail, Stake Pockets & Pipe Spools
- Cambered Spring Axles

- Multi-leaf Slipper Spring Suspension
- E-Z Lube Hubs
- 2 Electric Brake Axles
- 10k Drop-Leg Jack
- Treated Pine 2" x 8" Floor
- 4 Standard 3" D-Rings
- Black Mod Wheels*

- Lifetime LED Lighting
- All Lighting DOT Approved
- Molded Sealed Harness with Resistors
- 7-Way Receiver Female Plug with Adapter
- Powder Coat & Primer
- Dual Cylinder Lift
- 35" Deck Height


5500 FM 38N, BROOKSTON, TX 75421 • NORSTARCOMPANY.COM



WIDTH	LENGTH	GVWR	AXLES	TIRE/WHEEL	FRAME	WEIGHT
102	22	14,000	2 x 7,000 lb	235/80R16 8 Hole	8" I-Beam	4,300
102	24	14,000	2 x 7,000 lb	235/80R16 8 Hole	8" I-Beam	4,800
102	26	14,000	2 x 7,000 lb	235/80R16 8 Hole	8" I-Beam	5,070
102	28	14,000	2 x 7,000 lb	235/80R16 8 Hole	8" I-Beam	5,430
102	30	14,000	2 x 7,000 lb	235/80R16 8 Hole	8" I-Beam	5,680

^{*}WEIGHT OF UNITS ARE APPROXIMATES ONLY AND SUBJECT TO CHANGE DEPENDING ON OPTIONS

TOPI4 OPTIONAL FEATURES



V50

Blackwood Floor E03 12" Crossmembers K21 3" Adjustable Pintle Ring E01 T01 Weld on Spare Tire Mount R01 Winch Plate 1/2" (in floor) **Cold Weather Harness** W91



102" FULL DECK WIDTH



Scissor Hoist TH-516

