

# UTB03 MODEL

Single Axle Utility Trailer



**IRONBULL**  
A NEW BREED OF TRAILERS

## STANDARD FEATURES

- 1 - 3500 lb Axle (Idler)
- ST205/75 R15 (D) 8Ply
- Channel 4" x 4.5 lbs Frame & Tongue
- Angle 2.5" x 2.5" X 3/16" Crossmembers
- Tube 2" x 4" x 1/8" Rear Bumper
- Straight Deck (Std.)
- Tube Top Rail (Tube 2" x 2" x 1/8")
- 4' Fold-In Gate
- 4" Tail Gate w/ Springs (Tube 2" x 2" X 1/8" & Angle 2 1/2" x 2 1/2" x 3/16")
- Self-Retained Gate Pins
- Spring 7/16" wire
- DP Fender Step
- 2" A-Frame Coupler
- Jack Swivel Topwind 5k
- Teardrop Single Fender
- Treated Wood Floor
- C- Formed Front Bumper (Std.)
- Standard Wire Harness & 3/4" Lights
- Stake Pockets
- Tie Downs
- Spare Tire Mount
- Grey
- 21" Deck Height

*Taking the field by storm is the Iron Bull UTB. Our beefed up utility trailer packs a serious punch and is available in single or tandem axle configurations with the same heavy duty build that you have come to expect to get from Iron Bull.*

## BASE SPECS

WIDTH	LENGTH	GVWR	AXLES	TIRE/WHEEL	WEIGHT
83	12	3,500	1 x 3,500 lb	ST205/75R-15 LRD	1,500
83	14	3,500	1 x 3,500 lb	ST205/75R-15 LRD	

\*WEIGHT OF UNITS ARE APPROXIMATES ONLY AND SUBJECT TO CHANGE DEPENDING ON OPTIONS



**83"**  
Deck Width

**12' - 14'**  
Deck Lengths

**3,500 lbs**  
GVWR

**2,000 lbs**  
Load Capacity



Adjustable Coupler



4' Fold-In Gate



Fully LED Lighting With Fold-In Gate

5500 FM 38N, BROOKSTON, TX 75421 • NORSTARCOMPANY.COM