

DTB MODEL

Dual 6" I-Beam Dump Trailer



IRONBULL®

A NEW BREED OF TRAILERS



Strength where strength matters! Featuring the Side Armor™ body design, every DTB sits atop of a dual layer of 6" I-beam weighing in at 12 pounds per ft main frame construction. That's 24 lbs/ft of pure steel, putting maximum strength into the most critical part of your trailering system. Our 83" wide 14k bumper pull is by far our most popular model. With two 7k axles and tons of standard features, this model is a perfect fit for the contractor or weekend warrior.



BOX CAPACITY (CUBIC YARDS)			
SIZE	BASE	3FT.	4FT.
60x10	2.8		
72x10	4.4		
72x12	5.3	8.0	10.7
83x12	6.2	9.2	12.3
83x14	7.2	10.8	14.3
83x16	8.3	12.3	16.4

83"

Bed Width

12' - 16'

Bed Lengths

14,999 lbs

GVWR

9,626 - 10,370 lbs

Load Capacity

STANDARD FEATURES

- Side Armor™ Body Design
- ST235/80R16 Radial Tires
- Reinforced Top Rail
- Toolbox & Front Jack Bracket
- Dual 6" I-Beam Frame (24lbs/ft)
- 7 Gauge Steel Flooring on 83" Wide Models
- 4" Tubing Bed Frame
- Full Length Bed Runners & Ramp Pockets
- 10 Gauge 18" or 24" Steel Sides
- Standard Retractable Tarp Kit
- 10k Drop-Leg Jack
- 2 5/16" Adjustable Auto Latching Coupler
- 2 - 7k Cambered Brake Axles (8k & Triple 7 Available)
- Multi-leaf Slipper Spring Suspension
- Black Mod Wheels*
- Spare Tire Mount
- Slide-in Ramps
- Rear Support Stand Bracket
- Three-Way Spreader Gate
- Powder Coat & Primer
- Scissor Hoist with 516 Cylinder
- Double Acting Pump Unit w/ Gravity Down
- Flow Control Valve
- Locking Pump Box
- Standard Stake Pockets
- Weld On Diamond Plate Fenders
- Four Floor Mounted 1/2" D-Rings
- DOT Approved Lifetime LED Lighting
- Molded Sealed Harness with Resistors
- LED Voltage Indicator in Remote
- Built-In 5 amp Battery Charger
- 7-Way Receiver Female Plug w/ Adapter
- 32" Deck Height

5500 FM 38N, BROOKSTON, TX 75421 • NORSTARCOMPANY.COM



BASE SPECS

WIDTH	LENGTH	GVWR	AXLES	TIRE/WHEEL	SIDES	WEIGHT
60	10	9,990	2 x 5,200 lb	225/75R16 6 Hole	18"	2,800
72	10	9,990	2 x 5,200 lb	225/75R16 6 Hole	24"	3,682
72	12	9,990	2 x 5,200 lb	225/75R16 6 Hole	24"	4,057
72	12	14,999	2 x 7,000 lb	235/80R16 8 Hole	24"	4,149
83	12	14,999	2 x 7,000 lb	235/80R16 8 Hole	24"	4,629
83	14	14,999	2 x 7,000 lb	235/80R16 8 Hole	24"	4,960
83	16	14,999	2 x 7,000 lb	235/80R16 8 Hole	24"	5,373
83	16	21,000	3 x 7,000 lb	235/80R16 8 Hole	24"	5,373

*WEIGHT OF UNITS ARE APPROXIMATES ONLY AND SUBJECT TO CHANGE DEPENDING ON OPTIONS



Full Length Bed Runners



Rear Gate Latch



Side Armor™ System

DTB OPTIONAL FEATURES

CODE	DESCRIPTION
V53	3 Stage Telescopic Cylinder
082	Tandem 8k Axles
S01	Rear Support Stands
S61	3' Side Walls
S62	4' Side Walls
S90	Solar Panel Charger
R90	Wireless Remote
W91	Cold Weather Harness
J58	Hydraulic 12k Jack



WHERE DURABILITY MEETS AFFORDABILITY